

Vespa®

SPRINT S 150 ABS



42, Rue Brabant, Port-Louis - 4051150
www.maisondelamoto.mu

 MAISON DE LA
MOTO



SPRINT S 150 ABS

SPECIFICATIONS

ENGINE TYPE

Single-cylinder 4-stroke LEADER engine with catalytic converter, SOHC (single overhead cam), 3 valves per cylinder

DISPLACEMENT

154.8 cc

BORE/STROKE

58 mm / 58.6 mm

MAXIMUM POWER AT SHAFT

12.7 hp (9,5 KW) @ 7,750

ENGINE TORQUE, MAXIMUM

9.4 lb-ft (12,8 NM) @ 6,500 RPM

FUEL INJECTION

P.I. Injection (Port injected)

COOLING SYSTEM

Forced Air

STARTER

Electric

TRANSMISSION

Automatic twist and go (CVT with torque server)

CLUTCH

Automatic dry centrifugal clutch with vibration dampers

FRAME

Load bearing structure, sheet steel body with welded reinforcements

FRONT SUSPENSION

Single arm with coil spring and dual action monoshock absorber

REAR SUSPENSION

Coil spring with adjustable preload (4 settings), and dual action hydraulic monoshock

BRAKING SYSTEM

Front: 200 mm disc + ABS / Rear: 140 mm drum

TIRES

Front: Tubeless 110/70-12
Rear: Tubeless 120/70-12

DIMENSION

Length: 1,860 mm | Width: 735 mm

WHEELBASE

1,340 mm

SEAT HEIGHT

790 mm

FUEL CAPACITY

8 L

COLOURS

