

Vespa

GTS250



Maison de la Moto

www.maisondelamoto.mu • 42, Rue Brabant, Port-Louis Tel: 405 1150

 MAISON DE LA
MOTO

Vespa

GTS250



MAISON DE LA
MOTO

TECHNICAL SPECIFICATIONS

Engine	Single-cylinder 4-stroke, 4 valves. electronic injection, i-get	Front Suspension	Single-sided swingarm with coil spring & hydraulic control
Engine Capacity	125 cc	Rear Suspension	Double hydraulic shock absorber with four-position spring pre - load adjustment
Bore x stroke	52 mm x 58.7 mm	Front Brake	Hydraulically operated 220mm stainless steel disc
Max. power	10.3 kW - 14 HP at 8,750 rpm	Rear Brake	Hydraulically operated 220mm stainless steel disc
Max. Torque	12 Nm at 6,750 rpm	ABS/ASR System	As standard
Consumption	38.5 km/l	Front Tyre	Tubeless 120/70 - 12"
CO ₂ Emissions Cert.	60 g/km	Rear Tyre	Tubeless 130/70 - 12"
Fuel System	Electronic injection	Length / Width / Wheelbase	1.980 / 765 / 1,385 mm
Cooling	Liquid	Seat Height	790 mm
Ignition	Electric Start & Stop system	Fuel Tank Capacity	7 litres
Transmission	CVT with torque server	Emmissions Compliance	Euro 5+
Clutch	Automatic dry centrifugal clutch with vibration dampers		
Load Bearing Structure	Sheet metal body with welded structural reinforcements		