

DERBI®

STX/ETX 150



Tel: Belle Rose: 405 1150 / 405 1151 • Port Louis: 210 9520 • Email: mdml@emcar.mu

DERBI

STX150

ETX150

Engine type	Single-cylinder, 4-stroke	Single-cylinder, 4-stroke
Displacement	149 cc	149 cc
Bore and stroke	62 mm x 49.5mm	62 mm x 49.5mm
Timing gear	Single overhead cam, 2 valves	Single overhead cam, 2 valves
Starter	Electric	Electric
Lubrication	Dry sump	Dry sump
Fuel supply system	KEIHIN 22 mm carburetor	KEIHIN 22 mm carburetor
Cooling	Forced air	Forced air
Gearbox	5-speeds	5-speeds
Clutch	Multiplate wet clutch	Multiplate wet clutch
Frame	Single spar welded steel with pressed steel reinforcements	Single spar welded steel with pressed steel reinforcements
Front suspension	37 mm hydraulic forks	Upside down 37 mm hydraulic forks
Rear suspension	2 hydraulic shock absorbers with separate canisters, adjustable spring preload	2 hydraulic shock absorbers with separate canisters, adjustable spring preload
Front brake	Ø 240 mm disc with two piston caliper	Ø 260 mm daisy design disc with two piston caliper
Rear brake	104 mm drum	104 mm drum
Front wheel	Aluminium alloy 17" x 2.15	Spoked 17" x 2.15
Rear wheel	Aluminium alloy 17" x 2.75	Spoked 17" x 2.50
Front tyre	90/90-17" 49S	3.00-17 45P
Rear tyre	110/80-17" 57S	3.50-17 54P
Length	2000 mm	2030 mm
Width	760 mm	760 mm
Wheelbase	1330 mm	1340 mm
Fuel tank	18 litres	18 litres
Homologation	Euro 3	Euro 3



COLOURS

