

aprilia[®]

RS4 125/50



APRILIA

RS4 125

RS4 50

| | | |
|---------------------------|--|--|
| Engine type | Single-cylinder Four stroke liquid cooled Electronic injection 4 Valves | Single-cylinder Two stroke Liquid cooling |
| Displacement | 124.8 cc | 49.9 cc |
| Starter | Electric | Electric |
| Transmission | 6 speed | 6 speed |
| Frame | Aluminium perimeter frame | Twin spar aluminium frame |
| Front suspension | Ø 41 mm upside-down fork Wheel travel: 110 mm | Ø 41 mm upside-down fork Wheel travel: 110 mm |
| Rear suspension | Asymmetric swingarm Monoshock absorber Wheel travel: 130 mm | Asymmetric swingarm. Monoshock absorber. Wheel travel: 130 mm |
| Front brake | Ø 300 mm stainless steel disc Four-piston radial caliper | Ø 300 mm stainless steel disc Four-piston radial caliper |
| Rear brake | Ø 218 mm stainless steel disc Ø 30 mm single piston caliper. | Ø 218 mm stainless steel disc Ø 30 mm single piston caliper. |
| Tyres | Front: 110/80-17" Rear: 130/70 -17" | Front: 110/80-17" Rear: 130/70 -17" |
| Wheel rims | In light alloy with 6 split spokes Sealing profile for tubeless tyres | In light alloy with 6 split spokes Sealing profile for tubeless tyres |
| Dimensions | Length max: 1953mm Width max: 740mm Saddle height: 820mm | Length max: 1953mm Width max: 740mm Saddle height: 820mm |
| Fuel tank capacity | 14,5 litres (3.5 litres reserve) | 14,5 litres (3.5 litres reserve) |
| Emissions | Euro 3 | Euro 2 |



Colours ● ● ●